




Coal Tar Migration in a Multiaquifer Well at the Reilly Site – The Story of Well W23



Introduction and Background

- Allegation of waste injection via well(s) from old correspondence, lawsuit, and technical reports.
- How did W23 actually become contaminated?
- Reilly Site history.
- 1978 W23 Investigation.
- Multi-aquifer well hydraulics.
- 1980-82 W23 cleanout.
- Summary and conclusions.




PILE OF BEETS BY RAILROAD TRACK TOGETHER WITH FORCE EMPLOYED HANDLING BEETS, MINNESOTA SUGAR COMPANY, ST. LOUIS PARK, MINN.



Plant Water Supply

- Sugar beet plant used ~1 MGD.
- 1898 Hinckley well (~1000 feet deep).
- 8-12 shallow wells to fill cistern.
- Reilly drilled "backup" water supply well (W23) at refinery building.



RT&CC PLANT SITE BUILDING IDENTIFICATION

Description	Building No.			
Office and Laboratory	1			
Refinery	5-9			
Blacksmith Shop	10			
Locker and Change Room	11			
Garage	12			
By-Products Building	13			
Tar Shed	15			
Tank House	21			
Boiler House	22			
Treating Building	25			
Adzing and Boring Mill	26			
Garage	31			
Wash Room	33			
Tool House	37			




Figure A3-1 Plant Site Drawing From 1944 Blueprint

Totation	~ R;	03										
	W-2:3	,03 ~~.~	. St	- Lou	is Pa	rk				•		
Table No. of Fire of Pipe No. of Pipe	Togation			3		State	Minn	•				
Total Depth of Vol1 QOQ	Date Started Dec. 10, 1617	nes Statics Miss Miss Miss and a second of the Constant Line										
Dimputing of Soil 20 16 12 10 87 6 455 10TAL	ite Completed May 13, 1918	_0	or Kep			909						
DINNETER CF FAILE 20 16 12 10 87 6 17 10 10 10 10 10 10 10		Tut	al beg	th o.								
DIAMETER CF HOLE	MP = 874.5	1				8 1	-60	412 1	TATO			
2 80 227	DIAVENTR OF HOLD	20	16	12	10	. "7'						
Top of Fipe below Surface	Section 1		i		80	227						
No. of Ft. of Pipe in the Eule	Top of Fipe below Surface					373						
No. of Ft. of Flipe in the Este No. of Ft. of File brilled	Bottom of Pipe below Surface		-									
No. of Rt. of Eole Crilled	No. of Ft. of Pipe in the Hole		-	258	1175	15:6	i		909			
Depth of the Hole	No. of Ft. of Hole Drilled			2)0	1	1		i '		*		
Depth of the Hole				,	DEC.ATI	ON			Cunto	Form. Tren		
Depth of the Hole	TEST 1 2 3	1						-	-			
Depth to Vator at Rest 46 46 47 12 1 1 1 1 1 1 1 1	909 909 909	9 !	<u>Li</u> nest	one S	Grav	rel						
Depth to Vater Purping 63 80 27 27 210	Depth of the the		Limest	one								
Depth to Water Furnition 0	Denth to water at Nest	7	Sand !	Rock				1	1			
Size of Cylinder	Depth to Water Pumping											
Length of Streke 28 34% 24 Strokes per Ninute 25 43 1 49 Sand Rock Strokes per Ninute 150 500 1 530 Red Shale Gallons per Minute 150 500 1 530 Red Shale Vas Strainer in Hole Sand Rock Shaley Hard Rock Sand Rock Shaley Hard Rock Sand Rock Shaley Hard Rock Sand Rock Shale Shal	Depth of Pump Pipe							1 :	214	0.0		
Strokes per Hinute 25 43 49 Sand Rock Sand	Size of Cylinder	_	Red S	nale				1	220	0-7		
Strokes per Ninute 150 300 1 330 Sand Rock Shaley Sand Rock Sand R	Dengen of the second						•	6	226			
Vill well supply core Vas Strainer in Hole Fours putting in Purp Fours Pumping Fours taking out Pump Fours Consumed Strainer Strainer Fours Pumping Fours taking out Pump Fours Consumed Strainer	Strokes per Minute 25: 43 1 2	-						3	229			
Vill well supply core Vas Strainer in Hole Fours putting in Purp Fours Pumping Fours taking out Pump Fours Consumed Strainer Strainer Fours Pumping Fours taking out Pump Fours Consumed Strainer	Gallons per Minute 150 1500 1 33				Shale	y .		29	258			
Sand Rock Shaley Sand Rock Shale	Will well supply more	25				-		114	372	Obc		
Eours putting in Nump Eours Pumping Eours taking out Pump Hours Consumed Shale Shale Sand Rock Shale Shal	Vas Strainer in Hole	\dashv						85	457	€3		
Ecurs taking out Pump Shale Shale	Fours putting in Pump	\dashv			1 B00	k		50	507			
Hours Consumed Shale Sand Rock Shale STRATURE STRATURE Shale Sand Rock Shale	Fours Pumping				10 1101			138	645	£f.		
Hours Consumed Shale Sh	Hours taking out such	-			d Rock	c	,	67	712	€19		
Strain 2 Shaley Sand Rock Sand Rock Sand Rock Shale & Sand Rock Shale & Sand Rock Shale & Sand Rock Shale & Sand Rock WL = 33' 11/18 WL = 33' 11/18 Note: Note: The third test was made after the 10" pipe was cut off 80 feet - 6" Add: 1 by ERT. 15958.	1. 1	!	Shall	•					781			
Sand Rock Sand Rock Shale & Sand Rock Diameter Total Length No. of Ft. Exposed Vas Str. Sedged Did Sand come thru Str. Vas Str. coarse enough Style of Fittings NOTE: The third test was made after the 10" pipe was cut off 80 feet - 6" **Add: 1 by ERT. \$ 1909 £ ms. 2 909 £ ms. 2 909 £ ms. 2 909 £ ms. 3 11/78 **Add: 4 by ERT. 5 15958.			Shal	ey Sa	nd Ro	ck						
Make Diameter Total Length Number No. of Ft. Exposed Vas Str. Sedged Did Sand come thru Str. Vas Str. coarse enough Style of Fittings NOTE: The third test was made after the low pipe was cut off 80 feet - 60 **Add: 1 by ERT. \$ 15958.	cond Pock									-C ms		
Diameter Total Length Number No. of Ft. Exposed Vas Str. Sedged Did Sand come thru Str. Vas Str. coarse enough Style of Fittings NOTE: The third test was made after the low pipe was cut off 80 feet - 60 **Add: 4 by ERT. \$ Add: 4 by ERT. \$ Add: 4 by ERT.			Snal	e & S	and R	ock		1 -	1305			
Number No. of Ft. Exposed Vas Str. Sedged Did Sand come thru Str. Vas Str. coarse enough Style of Fittings NOTE: The third test was made after the low pipe was cut off 80 feet - 60 **Add: 1 by ERT. \$ Add: 1 by ERT. \$ 515958.	Yake		1					1	1	A		
Number No. of Ft. Exposed Vas Str. Sedged Did Sand come thru Str. Vas Str. coarse enough Style of Fittings NOTE: The third test was made after the 10" pipe was cut off 80 feet - 6" # Add: 1 by ERT. 515958.	Dianeter		1		-7		-,	-1	1 4	// · ·•		
Number No. of Ft. Exposed Vas Str. Sedged Did Sand come thru Str. Vas Str. coarse enough Style of Fittings NOTE: The third test was made after the 10" pipe was cut off 80 feet - 6" # Add: 1 by ERT. 515958.	Total Length		WL	= 3 3°	11/7			1	1	<i>!</i>		
Vas Str. Sedged Did Sand come thru Str. Vas Str. coarse enough Style of Fittings NOTE: The third test was made after the 10" pipe was cut off 80 feet - 6" **Add: 1 by ERT. below the surface. 515958.	Number		i —		/			1	1	<i>n</i>		
Vas Str. Sedged Did Sand come thru Str. Vas Str. coarse enough Style of Fittings NOTE: The third test was made after the 10" pipe was cut off 80 feet - 6" **Add: 1 by ERT. below the surface. 515958.	No. of Ft. Exposed		1					1		com		
NOTE: The third test was made after the 10" pipe was cut off 80 feet - 6" **Add: 1 by ERT. **Delow the surface.** 515958.**			1	•	-			1	1 '	1.0/.		
NOTE: The third test was made after the 10" pipe was cut off 80 feet - 6" below the surface. 515958.			-		•			1	1	.~W:		
NOTE: The third test was made after the 10" pipe was cut off 80 feet - 6" **Add: 1 by ERT. below the surface. 515958.			-{					1	1			
NOTE: The third test was made after the 10" pipe was cut off 80 feet - 6" ** Add: 1 by ERT. ** Delow the surface. 515958.			-					i	-1			
The third test was made after the 10" pipe was cut off 80 feet - 6" * Add. 1 by ERT. 515958.			=	1						: •		
The third test was made after the 10" pipe was cut off 80 feet - 6" * Add. 1 by ERT. 515958.			i									
6236 003 515958.	NOTE:		į.			+ 011	80 f	ret -	611			
6236 003 515958.	The third test was made after the 10" pipe was cut of the fat.											
323300G2 515950.	holow the Guriace.											
FIGURE 6-37 \ 6-62		:25	$\lesssim 0$	3						515750.		
			· FI	GURE, 6	5-37	1:00		6-62		***		



Reilly Site 1920s







1932 GW Problems

- SLP drilled its first municipal supply well
- Taste & odor problems after two weeks of pumping
- 10-inch casing added to W23 (to "seal" the Platteville)
- Memo from driller "waste creosote being drained down into the ground via several old wells"

McCarthy Well Company

EXPERIENCED AND DEPENDABLE SINCE 1860 NORTHWEST'S LARGEST WATER DEVELOPERS Minneapolis and St. Paul

Annersa Pres v To 670 EUSTIS ST.

ST. LOUIS PARK MINNESOTA.

well I Work west of C. 29 STP By mell

Dec. 15, 1954.

PROME: MESTOR 1554

This well always had a crosste taste to the water and we found at the Republic Creosoting Co. plant about one half mile away which were being and it was thought that this creosote was going down in these old wells and passing over thru the crevices in the Shakopee Dolomite and being pumped up into

two old abandoned wells... used to drain creosote down to the ground

mere with was coming from . They calked of possibly recasing this hole and drilling down to the Hinckley Sandrock, so as to get away from the creosote, and also perforating the 16" pipe up in the glacial drift, sand and gravel, and plugging off the maker rock below and taking water from the frift, with the possibility of getting away from the creesote, and another plan was to case off from the top of the Jordan sandrock to the surface, thereby shutting off the creosote from entering the well thru the Shakopee Dolomite crevices, so in Feb. 1955 we were employed by the village on a per hour basis to furnish 12" pipe and packer to shut off everything above the top of the Jordan Sandrock.

So we installed the packer and on top of the packer we had am 8 x 10 bushing, because the packer was threaded for standard 10" pipe, and on top of this bushing we had 197 feet of 8" pipe, and on top of this we had a swedge nipple out to 12" pipe, and on top of this we had 185'6" of 12" pipe, which brought the pipe up to the surface. We had to have 12" pipe in here because the bowls of the pump were of such size that it had to be a 12" hole where the pump was set. This is a Layne turbine.

Before setting the packer it was asiar 6919" to water. After setting the packer it was 76'8" to water, and on the following Monday morning, after the packer was set it was 78'5" to water, and when we set the packer it only settled 8" and came to a stop.

It was 68'9" to water before any packer or pipe was installed, so after packer was set we installed the turbine pump and the pump operated at 250 GPM 24 hours per day, and this is all the well would supply drawing the water down 125 below surface. This was pumping water out of the Jordan sandrock enly.

The village then kept pumping this well off and on for a period of over a month and they took various tests of the water, but the crocsote did not seem to clear up so ordered us to remove the pump and pipe and packer again, because we agreed to take this material all back again without charge to them. So when we went in to remove the packer we could not get the packer loose, and we had to jack on the pipe to start it loose. It jumped loose and the 8" pipe stripped out of the 8 x 10 cast bushing which was on top of the packer, and all of the pipe was

9600182




11

1950's "Tar Balls"


- New pump in 1955 automatic cycling.
- In 1956 pump seized; driller pulled pump.
- "Very effective solvent" supplied by Reilly (likely benzene)
- Re-occurrence within several months.
- Gravel was poured down the well to "hold down the tar"
- Well depth in 1966 was 610 feet.

Site Closure


- 1972 plant closed and sold to the City of St. Louis Park
- Hold harmless agreement
- Site demolished, graded
- Storm sewers, commercial, & residential redevelopment
- Lots of studies, esp. groundwater studies throughout the 1970's.
- Investigated Reilly's plant supply well: well W23.







Source: USGS WSP 2211







Figure 14. Schematic hydrologic section showing a well connecting two confined aquifers, flow through the well bore, and the effects of this flow on the potentiometric surfaces of the two aquifers

Source: USGS WSP 2211

Well W23 Cleanout

- Used cable tool methods to remove the plug of material for W23.
- Found a gravel layer between 653 and 665 feet deep.
- 50+ feet of tarry material had accumulated over the gravel after circa 1956.
- Plug removed but debris & sloughing prevented driller form reaching 909 feet.
- Removed the 10 inch casing that had been installed in 1932.





Conclusions

- Well 23 was not used as a disposal or injection well. Reilly did not pump or dump wastes down their water supply well.
- Creosote DNAPL migrated into the well via the Platteville prior to 1933 and along ungrouted casings.
- DNAPL and sediment formed a plug in the well due to bridging.
- Multi-aquifer flow aided contaminant migration into the Prairie du Chien – Jordan.

